

GL 1000

Our reliable platform lift with screw-driven system for passenger and goods traffic.

- GL 1000 lift for passenger and heavy goods traffic indoor and outdoor.
Suitable settings: industries, workshops, restaurants, shops, bars, hospitals, hotels etc.
- Capacity of 1000 kg.
- Shaft panels in filmlaminated steel sheet as standard performance.
- Easy to install.
- Advanced preassembly.
- Reasonable installation cost.
- Motorized emergency lowering system is standard equipment.
- Driving to next lower level during a power failure.
- Call with impulse drive.
- Door activated light relay.



GL 1000

Technical data: Indoor and outdoor lift for passenger and goods traffic.

STANDARD EQUIPMENT


Drive system	Screw-driven
Frequency control	Standard
Lifting capacity	1000 kg
Lifting height	0-13 m
Electrical connection	3-phase 400V 20A
Platform	1200x2100 mm (can be custom built)
Max. platform size	3,75 m ²
Shaft	1600x2200 mm
Pit or ramp	100 mm
Doors	A1 with electrical lock 1000x2000 mm
Surface treatment	Plastic film laminated hot galvanized sheet plating
Colour	Dobel 1072 broken white

OPTIONS

Shaft panels in safety glass	3 sides
Glass doors	Yes
- A2:1 WxH	650x950 mm
- A2 WxH	650x950 mm + 650x550 mm
- A3 WxH	650x1590 mm
Fire-proof doors	Yes
Doors with different width and height	Yes
Other platform width	Yes, max 3,75 m ²
Automatic door opener	Yes
Alarm telephone Safeline MX2	Std
Stainless	Yes
Different colour	Other Dobel colour
Key control	Yes
School control	Yes
UPS backup	Std
Remote controlled infralink	Yes
Outdoor variant	Yes
Call/send system	Yes



Retailer:



NAMI Lift AB

Box 36, SE-298 21 Tollarp, Sweden. T. +46 (0)44 31 33 44. F. +46 (0)44 31 01 35. www.nami.se