

# PL 400 STD

Our reliable platform lift with screw-driven system for passenger and small goods traffic.

PL 400 lift for passenger and small goods traffic.

Suitable settings: homes, schools, day nurseries, offices, shops, restaurants, hotels etc.

- Available for wheelchair users with lifting capacity of 400 kg.
- Shaft panels in film laminated steel sheet as standard performance. Tidy and durable.
- In principle the lift can be custom built according to your requirements.
- Easy to install.
- Advanced preassembly.
- Reasonable installation cost.
- Motorized emergency lowering system is standard equipment.
- Driving to the next lower level during a power failure.
- Call with impulse drive.
- Door activated light relay.



# PL 400 STD

Tekniska data: Handikapphiss för inom- och utomhusbruk.

## STANDARD EQUIPMENT

Drive system	Screw-driven
Frequency control	Standard
Lifting capacity	400 kg
Lifting height	0-13 m
Electrical connection	1-phase 240V 16A
Platform	1100x1500 mm (can be custom built)
Max. platform size	1.6 m <sup>2</sup>
Shaft	1400x1600 mm
Pit or ramp	50 mm
Doors	A1 with electrical lock, 900x2000 mm
Surface treatment	Plastic film laminated hot galvanized sheet plating
Colour	Dobel 1072 broken white


## OPTIONS

Shaft panels in safety glass	3 sides
Glass doors	Yes
- A2:1 WxH	650x950 mm
- A2 WxH	650x950 mm + 650x550 mm
- A3 WxH	650x1590 mm
Fire-proof doors	Yes
Automatic door opener	Yes
Alarm telephone Safeline MX2	Std
Stainless	Yes
Different colour	Other Dobel colour
Key control	Yes
School control	Yes
UPS backup	Std
Remote controlled infra link	Yes
Doors with different width and height	Yes
Other platform width	Yes, max width/length: 1100/1500 mm
Outdoor variant	Yes



STANDARD PANEL

Retailer:



NAMI Lift AB

Box 36, SE-298 21 Tollarp, Sweden. T. +46 (0)44 31 33 44. F. +46 (0)44 31 01 35. www.nami.se