

MSW B-LIFT

Robust platform lift for indoor and outdoor use.

- Further development of the well known B-lift.
- Suitable for all climates.
- Adjustable for different requirements.
- Easy to install.
- Low assembling costs.
- Electrical lock is standard equipment.
- Overload function.



MSW B-LIFT

Technical data: Indoor and outdoor lift for wheelchair users.

STANDARD EQUIPMENT


| | |
|-----------------------|-------------------------------------|
| Drive system | Screw-driven |
| Lifting capacity | 300 kg |
| Lifting height | 0-3,0 m |
| Lifting speed | 0,06 m/s |
| Electrical connection | 3-phase 380/240V 16A |
| Platform | 910x1400 mm |
| Shaft | 1260x1500 mm |
| Pit or ramp | 60 mm |
| Doors | Gate with electrical lock |
| Colour | Lacquered grey and galvanized sheet |
| Overload function | |

OPTIONS

| | |
|-------------------|-----|
| Frequency control | Yes |
| Alarm telephone | Yes |
| Other colour | Yes |
| Key control | Yes |



Retailer:



NAMI Lift AB

Box 36, SE-298 21 Tollarp, Sweden. T. +46 (0)44 31 33 44. F. +46 (0)44 31 01 35. www.nami.se